

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
18 October 2001 (18.10.2001)

PCT

(10) International Publication Number  
WO 01/77461 A1

(51) International Patent Classification<sup>7</sup>: E04F 15/04

(21) International Application Number: PCT/SE01/00779

(22) International Filing Date: 9 April 2001 (09.04.2001)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:  
0001325-0 10 April 2000 (10.04.2000) SE

(71) Applicant (for all designated States except US):  
VÄLINGE ALUMINIUM AB [SE/SE]; Kyrkogränd  
1, S-260 40 Viken (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): PERVAN, Darko  
[SE/SE]; Kyrkogränd 1, S-260 40 Viken (SE).

(74) Agent: AWAPATENT AB; Box 5117, S-200 71 Malmö  
(SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AT  
(utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE  
(utility model), DK, DK (utility model), DM, DZ, EE, EE  
(utility model), ES, FI, FI (utility model), GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,  
SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US,  
UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,  
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: LOCKING SYSTEM FOR FLOORBOARDS



(57) Abstract: The invention relates to a locking system for mechanical joining of floorboards (1, 1'), a floorboard having such a locking system and a flooring made of such floorboards. The locking system has mechanical cooperating means (36, 38; 6, 8, 14) for vertical and horizontal joining of adjoining floorboards. The means for horizontal joining about a vertical plane (F) comprise a locking groove (14) and a locking strip (16) which is located at opposite joint edge portions (4a, 4b) of the floorboard (4). The locking strip (6) projects from the joint plane (F) and has an upwards projecting locking element (8) at its free end. The locking groove (14) is formed in the opposite joint edge portion (4a) of the floorboard at a distance from the joint plane (F). The locking groove (14) and the locking element (8) have operative locking surfaces (10, 11). The locking surfaces are essentially plane and spaced from the upper side of the projecting strip and inside the locking groove and make a locking angle (A) of at least 50° to the upper side of the board. Moreover the locking groove has a guiding part (12) for cooperation with a corresponding guiding part (6) on the locking element (8).

WO 01/77461 A1

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
18 October 2001 (18.10.2001)

PCT

(10) International Publication Number  
WO 01/77461 A1

- (51) International Patent Classification<sup>7</sup>: E04F 15/04
- (21) International Application Number: PCT/SE01/00779
- (22) International Filing Date: 9 April 2001 (09.04.2001)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data:  
0001325-0 10 April 2000 (10.04.2000) SE
- (71) Applicant (for all designated States except US):  
VÄLINGE ALUMINIUM AB [SE/SE]; Kyrkogård  
1, S-260 40 Viken (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): PERVAN, Darko  
[SE/SE]; Kyrkogård 1, S-260 40 Viken (SE).
- (74) Agent: AWAPATENT AB; Box 5117, S-200 71 Malmö  
(SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AT  
(utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE  
(utility model), DK, DK (utility model), DM, DZ, EE, EE  
(utility model), ES, FI, FI (utility model), GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,  
SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US,  
UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,  
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: LOCKING SYSTEM FOR FLOORBOARDS



(57) Abstract: The invention relates to a locking system for mechanical joining of floorboards (1, 1'), a floorboard having such a locking system and a flooring made of such floorboards. The locking system has mechanical cooperating means (36, 38; 6, 8, 14) for vertical and horizontal joining of adjoining floorboards. The means for horizontal joining about a vertical plane (F) comprise a locking groove (14) and a locking strip (16) which is located at opposite joint edge portions (4a, 4b) of the floorboard (4). The locking strip (6) projects from the joint plane (F) and has an upwards projecting locking element (8) at its free end. The locking groove (14) is formed in the opposite joint edge portion (4a) of the floorboard at a distance from the joint plane (F). The locking groove (14) and the locking element (8) have operative locking surfaces (10, 11). The locking surfaces are essentially plane and spaced from the upper side of the projecting strip and inside the locking groove and make a locking angle (A) of at least 50° to the upper side of the board. Moreover the locking groove has a guiding part (12) for cooperation with a corresponding guiding part (6) on the locking element (8).

LOCKING SYSTEM FOR FLOORBOARDSTechnical Field

The invention generally relates to the field of mechanical locking of floorboards. The invention relates to an improved locking system for mechanical locking of floorboards, a floorboard provided with such an improved locking system, and a flooring made of such mechanically joined floorboards. The invention generally relates to an improvement of a locking system of the type described and shown in WO 9426999 and WO 9966151.

More specifically, the invention relates to a locking system for mechanical joining of floorboards of the type having a core and preferably a surface layer on the upper side of the core and a balancing layer on the rear side of the core, said locking system comprising: (i) for horizontal joining of a first and a second joint edge portion of a first and a second floorboard respectively at a vertical joint plane, on the one hand a locking groove which is formed in the underside of said second board and extends parallel with and at a distance from said vertical joint plane at said second joint edge and, on the other hand, a strip integrally formed with the core of said first board, which strip at said first joint edge projects from said vertical joint plane and supports a locking element, which projects towards a plane containing the upper side of said first floorboard and which has a locking surface for coaction with said locking groove, and (ii) for vertical joining of the first and second joint edge, on the one hand a tongue which at least partly projects and extends from the joint plane and, on the other hand, a tongue groove adapted to coact with said tongue, the first and second floorboards within their joint edge portions for the vertical joining having coacting upper and coacting lower contact surfaces, of

which at least the upper comprise surface portions in said tongue groove and said tongue.

#### Field of Application of the Invention

The present invention is particularly suitable for  
5 mechanical joining of thin floating floors of floorboards made up of an upper surface layer, an intermediate fibre-board core and a lower balancing layer, such as laminate flooring and veneer flooring with a fibreboard core. Therefore, the following description of the state of  
10 the art, problems associated with known systems, and the objects and features of the invention will, as a non-restricting example, focus on this field of application and, in particular, on rectangular floorboards with dimensions of about 1.2 m \* 0.2 m and a thickness of  
15 about 7-10 mm, intended to be mechanically joined at the long side as well as the short side.

#### Background of the Invention

Thin laminate flooring and wood veneer flooring are usually composed of a core consisting of a 6-9 mm fibre-board, a 0.20-0.8 mm thick upper surface layer and a  
20 0.1-0.6 mm thick lower balancing layer. The surface layer provides appearance and durability to the floorboards. The core provides stability and the balancing layer keeps the board level when the relative humidity (RH) varies  
25 during the year. The RH can vary between 15% and 90%. Conventional floorboards of the type are usually joined by means of glued tongue-and-groove joints (i.e. joints involving a tongue on a floorboard and a tongue groove on an adjoining floorboard) at the long and short sides.  
30 When laying the floor, the boards are brought together horizontally, whereby a projecting tongue along the joint edge of a first board is introduced into a tongue groove along the joint edge of the second adjoining board. The same method is used at the long side as well as the short  
35 side. The tongue and the tongue groove are designed for such horizontal joining only and with special regard to how glue pockets and gluing surfaces should be designed

to enable the tongue to be efficiently glued within the tongue groove. The tongue-and-groove joint presents coacting upper and lower contact surfaces that position the boards vertically in order to ensure a level surface of the finished floor.

In addition to such conventional floors, which are connected by means of glued tongue-and-groove joints, floorboards have recently been developed which are instead mechanically joined and which do not require the use of glue. This type of mechanical joint system is hereinafter referred to as a "strip-lock system", since the most characteristic component of this system is a projecting strip which supports a locking element.

WO 9426999 and WO 9966151 (owner Välinge Aluminium AB) disclose a strip-lock system for joining building panels, particularly floorboards. This locking system allows the boards to be locked mechanically at right angles to as well as parallel with the principal plane of the boards at the long side as well as at the short side. Methods for making such floorboards are disclosed in EP 0958441 and EP 0958442 (owner Välinge Aluminium AB). The basic principles of the design and the installation of the floorboards, as well as the methods for making the same, as described in the four above-mentioned documents, are usable for the present invention as well, and therefore these documents are hereby incorporated by reference.

In order to facilitate the understanding and description of the present invention, as well as the comprehension of the problems underlying the invention, a brief description of the basic design and function of the known floorboards according to the above-mentioned WO 9426999 and WO 9966151 will be given below with reference to Figs 1-3 in the accompanying drawings. Where applicable, the following description of the prior art also applies to the embodiments of the present invention described below.

Figs 3a and 3b are thus a top view and a bottom view respectively of a known floorboard 1. The board 1 is rectangular with a top side 2, an underside 3, two opposite long sides with joint edge portions 4a, 4b and two opposite short sides with joint edge portions 5a, 5b.

Without the use of the glue, both the joint edge portions 4a, 4b of the long sides and the joint edge portions 5a, 5b of the short sides can be joined mechanically in a direction D2 in Fig. 1c, so that they join in a joint plane F (marked in Fig. 2c). For this purpose, the board 1 has a flat strip 6, mounted at the factory, which strip extends throughout the length of the long side 4a and which is made of flexible, resilient sheet aluminium. The strip 6 projects from the joint plane F at the joint edge portion 4a. The strip 6 can be fixed mechanically according to the embodiment shown, or by means of glue, or in some other way. Other strip materials can be used, such as sheets of other metals, as well as aluminium or plastic sections. Alternatively, the strip 6 may be made in one piece with the board 1, for example by suitable working of the core of the board 1. The present invention is usable for floorboards in which the strip is integrally formed with the core, and solves special problems appearing in such floorboards and the making thereof. The core of the floorboard need not be, but is preferably, made of a uniform material. However, the strip 6 is always integrated with the board 1, i.e. it is never mounted on the board 1 in connection with the laying of the floor but it is mounted or formed at the factory. The width of the strip 6 can be about 30 mm and its thickness about 0.5 mm. A similar, but shorter strip 6' is provided along one short side 5a of the board 1. The part of the strip 6 projecting from the joint plane F is formed with a locking element 8 extended throughout the length of the strip 6. The locking element 8 has in its lower part an operative locking surface 10 facing the joint plane F and having a height of e.g.

0.5 mm. When the floor is being laid, this locking surface 10 coacts with a locking groove 14 formed in the underside 3 of the joint edge portion 4b of the opposite long side of an adjoining board 1'. The short side strip 6' is provided with a corresponding locking element 8', and the joint edge portion 5b of the opposite short side has a corresponding locking groove 14'. The edge of the locking grooves 14, 14' closest to the joint plane F forms an operative locking surface 11 for coaction with the operative locking surface 10 of the locking element.

Moreover, for mechanical joining of both long sides and short sides also in the vertical direction (direction D1 in Fig. 1c) the board 1 is formed with a laterally open recess 16 along one long side (joint edge portion 4a) and one short side (joint edge portion 5a). At the bottom, the recess 16 is defined by the respective strips 6, 6'. At the opposite edge portions 4b and 5b there is an upper recess 18 defining a locking tongue 20 coacting with the recess 16 (see Fig. 2a).

Figs 1a-1c show how two long sides 4a, 4b of two such boards 1, 1' on an underlay U can be joined together by means of downward angling. Figs 2a-2c show how the short sides 5a, 5b of the boards 1, 1' can be joined together by snap action. The long sides 4a, 4b can be joined together by means of both methods, while the short sides 5a, 5b - when the first row has been laid - are normally joined together subsequent to joining together the long sides 4a, 4b and by means of snap action only.

When a new board 1' and a previously installed board 1 are to be joined together along their long side edge portions 4a, 4b as shown in Figs 1a-1c, the long side edge portion 4b of the new board 1' is pressed against the long side edge portion 4a of the previous board 1 as shown in Fig. 1a, so that the locking tongue 20 is introduced into the recess 16. The board 1' is then angled downwards towards the subfloor U according to Fig. 1b. In this connection, the locking tongue 20 enters the recess



16 completely, while the locking element 8 of the strip 6 enters the locking groove 14. During this downward angling, the upper part 9 of the locking element 8 can be operative and provide guiding of the new board 1' towards the previously installed board 1. In the joined position as shown in Fig. 1c, the boards 1, 1' are locked in both the direction D1 and the direction D2 along their long side edge portions 4a, 4b, but the boards 1, 1' can be mutually displaced in the longitudinal direction of the joint along the long sides.

Figs 2a-2c show how the short side edge portions 5a and 5b of the boards 1, 1' can be mechanically joined in the direction D1 as well as the direction D2 by moving the new board 1' towards the previously installed board 1 essentially horizontally. Specifically, this can be carried out subsequent to joining the long side of the new board 1' to a previously installed board 1 in an adjoining row by means of the method according to Figs 1a-1c. In the first step in Fig. 2a, bevelled surfaces adjacent to the recess 16 and the locking tongue 20 respectively cooperate such that the strip 6' is forced to move downwards as a direct result of the bringing together of the short side edge portions 5a, 5b. During the final bringing together, the strip 6' snaps up when the locking element 8' enters the locking groove 14', so that the operative locking surfaces 10, 11 of the locking element 8' and of the locking groove 14' will engage each other.

By repeating the steps shown in Figs 1a-c and 2a-c, the whole floor can be laid without the use of glue and along all joint edges. Known floorboards of the above-mentioned type are thus mechanically joined usually by first angling them downwards on the long side, and when the long side has been secured, snapping the short sides together by means of horizontal displacement of the new board 1' along the long side of the previously installed board 1. The boards 1, 1' can be taken up in the reverse order of laying without causing any damage to the joint,

and be laid again. These laying principles are also applicable to the present invention.

For optimal function, subsequent to being joined together, the boards should be capable of assuming a position along their long sides in which a small play can exist between the operative locking surface 10 of the locking element and the operative locking surface 11 of the locking groove 14. Reference is made to WO 9426999 for a more detailed description of this play. Such a play can be in the order of 0.01-0.05 mm between the operative locking surfaces 10, 11 when pressing the long sides of adjoining boards against each other. However, there need not be any play at the upper edge of the joint edges at the upper side of the floorboards.

In addition to what is known from the above-mentioned patent specifications, a licensee of Välinge Aluminium AB, Norske Skog Flooring AS, Norway (NSF), introduced a laminated floor with mechanical joining according to WO 9426999 in January 1996 in connection with the Domotex trade fair in Hannover, Germany. This laminated floor, which is shown in Fig. 4a and is marketed under the trademark Alloc<sup>®</sup>, is 7.2 mm thick and has a 0.6-mm aluminium strip 6 which is mechanically attached on the tongue side. The operative locking surface 10 of the locking element 8 has an inclination (hereinafter termed locking angle) of about 80° to the plane of the board. The locking element has an upper rounded guiding part and a lower operative locking surface. The rounded upper guiding part, which has a considerably lower angle than the locking surface, contributes significantly to positioning of the boards in connection with installation and facilitating the sliding-in of the locking element into the locking groove in connection with angling and snap action. The vertical connection is designed as a modified tongue-and-groove joint, the term "modified" referring to the possibility of bringing the tongue groove and tongue together by way of angling.

WO 9747834 (owner Unilin Beeher B.V., the Netherlands) describes a strip-lock system which has a fibre-board strip and is essentially based on the above known principles. In the corresponding product, "Uniclic<sup>®</sup>",  
5 which this owner began marketing in the latter part of 1997 and which is shown in Fig. 4c, one seeks to achieve biasing of the boards. This results in high friction and makes it difficult to angle the boards together and to displace them. The document shows several embodiments of  
10 the locking system. All locking surfaces have an angle that does not exceed 60° and the joint systems have no guiding surfaces.

Other known locking systems for mechanical joining of board materials are described in, for example, GB-A-  
15 2,256,023 showing unilateral mechanical joining for providing an expansion joint in a wood panel for outdoor use. The locking system does not allow joining of the joint edges and is not openable by upward angling round the joint edges. Moreover the locking element and the  
20 locking groove are designed in a way that does not provide sufficient tensile strength. US-A-4,426,820 (shown in Fig. 4e) which concerns a mechanical locking system for a plastic sports floor, which floor is intentionally designed in such manner that neither displacement of the  
25 floorboards along each other nor locking of the short sides of the floorboards by snap action is allowed.

In the autumn of 1998, NSF introduced a 7.2-mm laminated floor with a strip-lock system which comprises a fibreboard strip and is manufactured according  
30 to WO 9426999 and WO 9966151. This laminated floor is marketed under the trademark "Fiboloc<sup>®</sup>" and has the cross-section illustrated in Fig. 4b.

In January 1999, Kronotex GmbH, Germany, introduced a 7.8 mm thick laminated floor with a strip lock under  
35 the trademark "Isilock<sup>®</sup>". A cross-section of the joint edge portion of this system is shown in Fig. 4d. Also

in this floor, the strip is composed of fibreboard and a balancing layer.

During 1999, the mechanical joint system has obtained a strong position on the world market, and some twenty manufacturers have shown, in January 2000, different types of systems which essentially are variants of Fiboloc<sup>®</sup>, Uniclic<sup>®</sup> and Isilock<sup>®</sup>. All systems have locking surfaces with low locking angles and the guiding, in the cases where it occurs, is to be found in the upper part of the locking element.

#### Summary of the Invention

Although the floors according to WO 9426999 and WO 99/66151 and the floor sold under the trademark Fiboloc<sup>®</sup> exhibit major advantages in comparison with traditional, glued floors, further improvements are desirable mainly in thin floor structures.

The vertical joint system, which comprises locking elements and locking grooves, has two coacting parts, viz. a locking part with operative locking surfaces which prevent the floorboards from sliding apart, and a guiding part, which positions the boards and contributes to the locking element being capable of being inserted into the locking groove. The greater the angular difference between the locking surface and the guiding part, the greater the guiding capacity.

The preferred embodiment of the locking element according to WO 9426999, having a rounded upper part and an essentially perpendicular lower locking surface, is ideal for providing a joint of high strength. The inward angling and snapping-in function is also very good and can be achieved with completely tight joint edges owing to the fact that the strip is bent downwards, whereby the locking element opens and snaps into the locking groove.

The drawback of this design of the locking element is the taking-up function, which is a vital part in most mechanical locking systems. The locking groove follows a circular arc with its centre in an upper joint edge

(i.e. where the vertical joint plane intersects the upper side of the floorboard). If the locking groove has a locking angle corresponding to the tangent to the circular arc, below referred to as clearance angle, taking-up  
5 can be carried out without problems. If the locking angle is greater than the clearance angle, the parts of the locking system will overlap each other in upward angling, which makes the taking-up considerably more difficult.

Alloc<sup>®</sup> (see Fig. 4a) has an aluminium strip with a  
10 locking angle of about 80° and a clearance angle of about 65°. The other known systems with strips made integrally with the core of the floorboard have locking angles and clearance angles of 30-55° owing to the width of the strip being narrower and the radius of the circular arc  
15 being smaller. This results in low tensile strength in the horizontal direction D2 since the locking element easily slides out of the locking groove. Moreover, the horizontal tensile stress will be partly converted into an upwardly directed force which may cause the edges to  
20 rise. This basic problem will now be explained in more detail.

When the relative humidity, RH, changes from about 80% in summer to about 20% in winter, the floating floor shrinks by about 10 mm in a normal room. The motion takes  
25 place in a concealed manner under the skirting board at the surrounding walls. This shrinkage will move all furniture which exerts a load onto the floor. Tests have shown that if a room is fitted with heavy bookcases along the walls, the joint will be subjected to very high load  
30 or tensile stress in winter. At the long side this load may amount to about 300 kg/running metre of joint. At the short side where the load is distributed over a smaller joint width, the load may amount to 500 kg/running metre.

If the locking surfaces have a low locking angle,  
35 the strength of the joint will be reduced to a considerable extent. In winter the joint edges may slide apart so that undesirable visible joint gaps arise on the upper

side of the floor. Besides, the angled locking surface of the locking element will press the upper locking surface of the locking groove upwards to the joint surface. The upper part of the tongue will press the upper part of the tongue groove upwards, which results in undesirable rising of the edges. The present invention is based on the understanding that these problems can be reduced to a considerable extent, for example, by making the locking surfaces with high locking angles exceeding  $50^\circ$  and, for instance, by the locking surfaces being moved upwards in the construction. The ideal design is perpendicular locking surfaces. Such locking surfaces, however, are difficult to open, especially if the strip is made of fibre-board and is not as flexible as strips of e.g. aluminium.

Perpendicular locking surfaces can be made openable if interaction between a number of factors is utilised. The strip should be wide in relation to the floor thickness and it should have good resilience. The friction between the locking surfaces should be minimised, the locking surface should be small and the fibre material in the locking groove, locking element and upper joint edges of the locking system should be compressible. Moreover, it is advantageous if the boards in the locked position can assume a small play of a few hundredths of a millimetre between the operative locking surfaces of the locking groove and the locking element if the long side edge portions of the boards are pressed together.

There are today no known products or methods which give sufficiently good solutions to problems which are related to essentially perpendicular locking surfaces which are at the same time easy to open.

It would be a great advantage if openable locking surfaces could be made with greater degrees of freedom and a high locking angle, preferably  $90^\circ$ , in combination with narrow strips which reduce waste in connection with working. The manufacture would be facilitated since working tools would only have to be guided accurately in

the horizontal direction and the joint would obtain high strength.

To sum up, there is a great need for providing a locking system which takes the above-mentioned requirements, problems and desiderata into consideration to a greater extent than prior art. The invention aims at satisfying this need.

An object of the present invention therefore is to provide a locking system having

- 10 (i) locking surfaces with a high locking angle and high strength,
- (ii) a horizontal joint system which has such locking surfaces and which at the same time is openable, and
- 15 (iii) a horizontal joint system which has such locking surfaces and at the same time comprises guiding parts for positioning of the floorboards.

The invention is based on a first understanding that the identified problems must essentially be solved with a locking system where the locking element has an operative locking surface in its upper part instead of in its lower part as in prior-art technique. When taking up an installed floor by upward angling, the locking surface of the locking groove will therefore exert a pressure on the upper part of the locking element. This results in the strip being bent backwards and downwards and the locking element being opened in the same way as in inward angling. In a suitable design of locking element and locking groove, this pressure can be achieved in a part of the locking element which is closer to the top of the locking element than that part of the locking element which is operative in the locked position. In this way, the opening force will be lower than the locking force.

The invention is also based on a second understanding which is related to the motions during upward angling and taking-up of an installed floor. The clearance angling, i.e. the tangent to a circular arc with its centre

where the vertical joint plane intersects the upper side of the floorboard, is higher in the upper part of the locking element than in its lower part. If a part of the locking surface, which in prior-art technique is placed in the lower part of the locking element and the locking groove respectively, is placed in the upper part instead according to the invention, the difference in degree between the locking angle and the clearance angle will be smaller, and the opening of the locking when taking up an installed floor will be facilitated.

The invention is also based on a third understanding which is related to the guiding of the floorboards during inward angling when the floor is to be laid. Guiding is of great importance in inward angling of the long sides of the floorboards since the floorboards have often warped and curved and therefore are somewhat arcuate or in the shape of a "banana". This shape of a banana can amount to some tenths of a millimetre and is therefore not easily visible to the naked eye in a free board. If the guiding capacity of the locking system exceeds the maximum banana shape, the boards can easily be angled downwards, and they need not be pressed firmly against the joint edge in order to straighten the banana shape and allow the locking element to be inserted into the locking groove. In prior-art locking systems, the guiding part is formed essentially in the upper part of the locking element, and if the locking surface is moved up to the upper part, it is not possible to form a sufficiently large guiding part. A sufficiently great and above all more efficient and reliable guiding is achieved according to the invention by the guiding part being moved to the locking groove and its lower part. According to the invention it is even possible to form the entire necessary guiding in the lower part of the locking groove. In preferred embodiments, coacting guiding parts can also be formed both in the upper part of the locking element and the lower part of the locking groove.



According to a first aspect of the invention, a locking system is provided of the type which is stated by way of introduction and which according to the invention is characterised by the combination that the locking element has at least one operative locking surface which is positioned in the upper part of the locking element, that this operative locking surface is essentially plane and in relation to the plane of the boards has an angle (A) which exceeds  $50^\circ$ , that the locking groove has at least one locking surface which is essentially plane and which cooperates with said locking surface of the locking element, that the locking groove has a lower inclined or rounded guiding part which guides the locking element into the locking groove by engagement with a portion of the locking element which is positioned above the locking surface of the locking element or adjacent to its upper edge.

The invention concerns a locking system for mechanical joining of floorboards and a floorboard having such a locking system. The locking system has mechanical cooperating means for vertical and horizontal joining of adjoining floorboards. The means for horizontal joining about a vertical joint plane comprise a locking groove and a locking strip which are positioned at the opposite joint edge portions of the floorboard. The locking strip extends from the joint plane and has an upwardly projecting locking element at its free end. The locking groove is formed in the opposite joint edge portion of the floorboard at a distance from the joint plane. The locking groove and the locking element have operative locking surfaces. These locking surfaces are essentially plane and positioned at a distance from the upper side of the projecting strip and in the locking groove and form an angle of at least  $50^\circ$  to the upper side of the board. Moreover, the locking groove has a guiding part for cooperation with a corresponding guiding part of the locking element.

Brief Description of the Drawings

- Figs 1a-c show in three stages a downward angling method for mechanical joining of long sides of floorboards according to WO 9426999.
- 5 Figs 2a-c show in three stages a snap-action method for mechanical joining of short sides of floorboards according to WO 9426999.
- Figs 3a-b are a top plan view and a bottom view respectively of a floorboard according to WO  
10 9426999.
- Figs 4a-e show four strip-lock systems available on the market and a strip-lock system according to US 4,426,820.
- Fig. 5 shows in detail the basic principles of a  
15 known strip-lock system for joining of the long sides of floorboards according to WO 9966151.
- Fig. 6 shows a variant of a locking system (applicant Valinge Aluminium AB) for which protection is sought and which has not yet been published.
- 20 Figs 7+8 illustrate a locking system according the invention.
- Fig. 9 shows another example of a floorboard and a locking system according to the present invention.  
25
- Figs 10-12 show variants of a locking groove and a locking component of three further examples of a floorboard and a locking system according to the present invention.

30 Description of Preferred Embodiments

Prior to the description of preferred embodiments, with reference to Fig. 5, a detailed explanation will first be given of the most important parts in a strip lock system.

- 35 The invention can be applied in joint systems with a worked strip which is made in one piece with the core of the board, or with a strip which is integrated with

the core of the board but which has been made of a separate material, for instance aluminium. Since the worked embodiment, where strip and core are made of the same material, constitutes the greatest problem owing to  
5 higher friction and poorer flexibility, the following description will focus on this field of application.

The cross-sections shown in Fig. 5 are hypothetical, not published cross-sections, but they are fairly similar to the locking system of the known floorboard "Fiboloc®"  
10 and to the locking system according to WO 9966151. Accordingly, Fig. 5 does not represent the invention but is only used as a starting point of a description of the technique for a strip lock system for mechanical joining of adjoining floorboards. Parts corresponding to those in  
15 the previous Figures are in most cases provided with the same reference numerals. The construction, function and material composition of the basic components of the boards in Fig. 5 are essentially the same as in embodiments of the present invention, and consequently, where  
20 applicable, the following description of Fig. 5 also applies to the subsequently described embodiments of the invention.

In the embodiment shown, the boards 1, 1' in Fig. 5 are rectangular with opposite long side edge portions 4a, 4b and opposite short side edge portions 5a, 5b. Fig. 5  
25 shows a vertical cross-section of a part of a long side edge portion 4a of the board 1, as well as a part of a long side edge portion 4b of an adjoining board 1'. The boards 1 have a core 30 which is composed of fibreboard and which supports a surface layer 32 on its front side  
30 (upper side) and a balancing layer 34 on its rear side (underside). A strip 6 is formed from the core and balancing layer of the floorboard by cutting and supports a locking element 8. Therefore the strip 6 and the lock-  
35 ing element 8 in a way constitute an extension of the lower part of the tongue groove 36 of the floorboard 1. The locking element 8 formed on the strip 6 has an ope-

operative locking surface 10 which cooperates with an operative locking surface 11 in a locking groove 14 in the opposite long side edge portion 4b of the adjoining board 1'. By the engagement between the operative locking surfaces 10, 11 a horizontal locking of the boards 1, 1' transversely of the joint edge (direction D2) is obtained. The operative locking surface 10 of the locking element 8 and the operative locking surface 11 of the locking groove 14 form a locking angle A with a plane parallel with the upper side of the floorboards. This locking angle A of 60° corresponds to the tangent to a circular arc C which has its centre in the upper joint edge, i.e. the intersection between the joint plane F and the upper side of the boards, and which passes the operative locking surfaces 10, 11. In upward angling of the floorboard 1' relative to the floorboard 1, the locking groove will follow the circular arc C, and taking-up can therefore be made without resistance. The upper part of the locking element has a guiding part 9, which in installation and inward angling guides the floorboard to the correct position.

To form a vertical lock in the D1 direction, the joint edge portion 4a has a laterally open tongue groove 36 and the opposite joint edge portion 4b has a laterally projecting tongue 38 which in the joined position is received in the tongue groove 36. The upper contact surfaces 43 and the lower contact surfaces 45 of the locking system are also plane and parallel with the plane of the floorboard.

In the joined position according to Fig. 5, the two juxtaposed upper portions 41 and 42 of the surfaces, facing each other, of the boards 1, 1' define a vertical joint plane F.

Fig. 6 shows an example of an embodiment according to the invention, which has not yet been published and which differs from the embodiment in Fig. 5 by the tongue 38 and the tongue groove 36 being displaced downwards in

the floorboard so that they are eccentrically positioned. Moreover, the thickness of the tongue 38 (and, thus, the tongue groove 36) has been increased while at the same time the relative height of the locking element 8 has been retained. Both the tongue 38 and the material portion above the tongue groove 36 are therefore significantly more rigid and stronger while at the same time the floor thickness T, the outer part of the strip 6 and the locking element 8 are unchanged.

Fig. 7 shows a first embodiment of the present invention. The locking element 8 has a locking surface 10 with a locking angle A which is essentially perpendicular to the plane of the floorboards. The locking surface 10 has been moved upwards relative to the upper side of the strip 6, compared with prior-art technique.

The locking angle A in this embodiment of the invention is essentially greater than a clearance angle TA, which corresponds to the tangent to a circular arc C1 which is tangent to the upper part of the locking element 8 and which has its centre C3 where the joint plane F intersects the upper side of the boards.

Since the edge of the locking groove 14 closest to the joint plane F has portions which are positioned outside the circular arc C1 to be able to retain the locking element 8 in the locking groove, these portions will, in taking-up of the floorboard 1', follow a circular arc C2 which is concentric with and has a greater diameter than the circular arc C1 and which intersects the lower edge of the operative locking surface 11 of the locking groove. Taking-up of the floorboard 1' by upward angling requires that the strip 6 can be bent or that the material of the floorboards 1, 1' can be compressed.

In a preferred embodiment of the invention, the boundary surface of the locking groove 14 closest to the joint plane F has a lower guiding part 12 which is positioned inside the circular arc C1 and which will therefore efficiently guide the locking element 8 in

connection with the laying of the floor and the downward angling of the floorboard 1' relative to the floorboard 1.

Fig. 7 also shows that the operative locking surface 11 of the locking groove 14 and the operative locking surface 10 of the locking element 8 have been moved upwards in the construction and are located at a distance from the upper side of the locking strip 6. This positioning brings several advantages which will be discussed in the following.

As is also evident from Fig. 7, there is an inclined surface 13 between the upper side of the locking strip 6 and the lower edge of the operative locking surface 10 of the locking element 8. In this shown embodiment, there is a gap between this inclined surface 13 and the guiding part 12 of the locking groove 14, so that the transition of the guiding part to the underside of the edge portion 4b is located inside the circular arc C1. Owing to such a gap, the friction is reduced in mutual displacement of the floorboards along the joint plane F in connection with the laying of the floor.

Fig. 8 shows how upward angling can take place when taking up an installed floor. The locking surface 11 of the locking groove exerts a pressure on the upper part of the operative locking surface 10 of the locking element 8. This pressure bends the strip 6 downwards and the locking element 8 backwards and away from the joint plane F. In practice, a marginal compression of the wood fibres in the upper joint edge surfaces 41, 42 of the two floorboards and of the wood fibres in the locking surface 10 of the locking element and the locking surface 11 of the locking groove takes place. If the joint systems are besides designed in such manner that the boards in their locked position can assume a small play of some hundredths of a millimetre between the locking surfaces 10, 11, opening by upward angling can take place as

reliably and with the same good function as if the locking surfaces were inclined.

Fig. 9 shows another embodiment of the invention. In this embodiment, the groove 36 and the tongue 38 have  
5 been made shorter than in the embodiment according to Figs 7 and 8. As a result, the mechanical locking of two adjoining floorboards 1, 1' can be carried out both by vertical snap action and by inward angling during the bending of the strip. The vertical snap action can also  
10 be combined with known shapes of locking surfaces and with a possibility of displacement along the joint direction in the locked position and also taking-up by pulling out along the joint edge or upward angling. However, the Figure shows the floorboards during inward angling of the  
15 floorboard 1'. The lower part or guiding part 12 of the locking groove guides the floorboards and enables the introduction of the locking element 8 into the locking groove 14 so that the locking surfaces 10, 11 will engage each other. The strip 6 is bent downwards and the locking  
20 element 8 is guided into the locking groove although the edge surface portions 41, 42, facing each other, of the floorboards are spaced apart. The locking angle A is in this embodiment about 80°. The bending of the strip can be facilitated by working the rear side of the strip, so  
25 that a part of the balancing layer 34 between the joint plane F and the locking element 8 is wholly or partly removed.

Fig. 10 shows an enlargement of the locking element 8 and the locking groove 14. The locking element 8 has an  
30 operative upper locking surface 10 which is formed in the upper part of the locking element at a distance from the upper side of the locking strip 6. The locking groove 14 has a cooperating operative locking surface 11 which has also been moved upwards and which is at a distance from  
35 the opening of the locking groove 14.

Operative locking surfaces relate to the surfaces 10, 11 which, when locked and subjected to tension load,

cooperate with each other. Both surfaces are in this embodiment plane and essentially at right angles to the principal plane of the floorboards. The locking groove has a guiding part 12 which is located inside the previously mentioned circular arc C1 and which in this embodiment is tangent to the upper part of the operative locking surface 10 of the locking element 8.

In this embodiment, the locking element has in its upper part a guiding part 9 which is located outside the circular arc C1. The guiding parts 9, 12 of the locking element and the locking groove respectively contribute to giving the joint system a good guiding capacity. The total lateral displacement of the floorboards 1, 1' in the final phase of the laying procedure is therefore the sum of E1 and E2 (see Fig. 10), i.e. the horizontal distance between the lower edge of the guiding part 12 and the circular arc C1 and between the upper edge of the guiding part 9 and the circular arc C1. This sum of E1 and E2 should be greater than the above-mentioned maximum banana shape of the floorboards. For the joint system to have a guiding capacity, E1 and E2 must be greater than zero, and both E1 and E2 can have negative values, i.e. be positioned on the opposite side of the circular arc C1 relative to that shown in the Figure.

The guiding capacity is further improved if the strip 6 is bendable downwards and if the locking element 8 is bendable away from the joint plane so that the locking surface 10 of the locking element can open when the locking element comes into contact with a part of the other board. A free play between surfaces which are not operative in the locking system facilitates manufacture since such surfaces need not be formed with narrow tolerances. The surfaces which are operative in the locking system and which are intended to engage each other in the laid floor, i.e. the operative locking surfaces 10, 11, the edge surface portions 41, 42 and the upper contact surfaces 43 between the groove 36 and the tongue 38 must,



however, be manufactured with narrow tolerances both as regards configuration and as regards their relative positions.

5 If the inoperative surfaces in the locking system are spaced from each other, the friction in connection with lateral displacement of joined floorboards along the joint edge will decrease.

10 According to the invention, the operative locking surfaces 10, 11 of the locking element and in the locking groove have been formed with a small height, seen perpendicular to the principal plane of the floorboards. This also reduces the friction in lateral displacement of joined floorboards along the joint edge.

15 By the operative locking surfaces according to the invention being made essentially plane and parallel with the joint plane F, the critical distance between the joint plane F and the locking surface 10 and 11, respectively, can easily be made with very high precision, since the working tools used in manufacture need only be controlled with high precision essentially horizontally. The tolerance in the vertical direction only affects the height of the operative locking surfaces but the height of the locking surfaces is not as critical as their position in the horizontal direction. Using modern manufacturing technique, the locking surface can be positioned in relation to the joint plane with a tolerance of  $\pm 0.01$  mm. At the same time the tolerance in the vertical direction can be  $\pm 0.1$  mm, which results in, for instance, the height of the operative locking surfaces varying between 0.5 mm and 0.3 mm. Tensile tests have demonstrated that operative locking surfaces with a height of 0.3 mm can give a strength corresponding to 1000 kg/running metre of joint. This strength is considerably higher than required in a normal floor joint. The height H of the locking element 8 above the upper side of the strip 6 and the width W of the locking element 8 on a

20  
25  
30  
35

level with the operative locking surface are important to the strength and the taking-up of the floorboards.

At the long side where the strength requirements are lower, the locking element can be made narrower and higher. A narrow locking element bends more easily and facilitates removal of installed floorboards.

At the short side where the strength requirements are considerably higher, the locking element should be low and wide. The lower front part 13 of the locking element, i.e. the locking element portion between the lower edge of the locking surface 10 and the upper side of the strip 6, has in this embodiment an angle of about 45°. Such a design reduces the risk of cracking at the border between the upper side of the strip 6 and the locking element 8 when subjecting the installed floor to tensile load.

Fig. 11 shows another embodiment of the invention. In this case, use is made of a locking element 8 which has an upper operative locking surface 10 with an angle of about 85° which is greater than the clearance angle, which is about 75°. In this embodiment, the guiding part 12 of the locking groove 14 is also used as a secondary locking surface which supplements the operative locking surfaces 10, 11. This embodiment results in very high locking forces. The drawback of this embodiment, however, is that the friction in connection with relative displacement of the floorboards 1, 1' in the lateral direction along the joint plane F will be considerably greater.

Fig. 12 shows one more embodiment with essentially perpendicular locking surfaces 10, 11 and small guiding parts 9, 12, which makes it necessary to bend the strip 6 in connection with laying of the floorboards. The joint system is very convenient for use at the short sides of the floorboards where the need for guiding is smaller since in practice there is no "banana shape". Opening of the short side can be effected by the long sides first

being angled upwards, after which the short sides are displaced in parallel along the joint edge. Opening can also be effected by upward angling if the locking groove and the locking element have suitably designed guiding parts 12, 9 which are rounded or which have an angle less than  $90^\circ$ , and if the operative locking surfaces 10, 11 have a small height LS (Fig. 12), so that their height is less than half the height of the locking element. In this embodiment, E2 is greater than E1, which makes the sum of E2 and E1 greater than zero (E1 represents in this case a negative value). If in this case E1 and E2 should be of almost the same size, the guiding may be effected by downward bending of the strip 6, which automatically causes displacement of the guiding part 9 of the locking element 8 away from the intended joint plane F and also causes a change in angle of the locking element 8 so that guiding takes place.

Several variants of the invention are feasible. The joint system can be manufactured with a large number of different joint geometries, some or all of the above parameters being made different, especially when it is desirable to give priority to a certain property over the other properties.

The owner has taken into consideration and tested a number of variants based on that stated above.

The height of the locking element and the angle of the locking surfaces can be varied. Nor is it necessary for the locking surface of the locking groove and the locking surface of the locking element to have the same inclination or configuration. Guiding parts can be made with different angles and radii. The height of the locking element can vary over its width in the principal plane of the floorboard, and the locking element can have different widths at different levels. The same applies to the locking groove. The locking surface of the locking groove can be made with a locking angle exceeding  $90^\circ$  or be made slightly rounded. If the locking surfaces of the

locking element is made with an angle exceeding  $90^\circ$ , taking-up of the floorboards by upward angling can be prevented and permanent locking can be achieved. This can also be achieved with a joint system having  $90^\circ$  locking surfaces which are sufficiently large or in combination with specially designed guiding parts which counteract upward angling. Such locking systems are particularly suited for short sides which require a high locking force.

## CLAIMS

1. A locking system for mechanical joining of floorboards (1, 1') having a core (30) and opposite first and second joint edge portions (4a, 5a and 4b, 5b, respectively), adjoining floorboards (1, 1') in the mechanically joined position having their first and second joint edge portion (4a, 5a and 4b, 5b, respectively) joined at a vertical joint plane (F), said locking system comprising
- a) for vertical joining of the first joint edge portion (4a) of a first floorboard (1) and the second joint edge portion (4a, 5a and 4b, 5b, respectively), of an adjoining second floorboard (1'), mechanical cooperating means (36, 38), and
  - b) for horizontal joining of the first and second joint edge portions (4a, 5a and 4b, 5b, respectively), mechanical cooperating means (6, 8; 14) which comprise
    - a locking groove (14) formed in the underside (3) of said second floorboard (1') and extending parallel with and at a distance from the vertical joint plane (F) at said second joint edge portion (4b, 5b) and having a downward directed opening, and
    - a strip (6) integrally formed with the core of said first floorboard (1), which strip at said first joint edge portion (4a, 5a) projects from said vertical joint plane (F) and at a distance from the joint plane (F) has a locking element (8) which projects towards a plane containing the upper side of said first floorboard (1) and which has at least one operative locking surface (10) for coaction with said locking groove (14),
- the locking groove (14), seen in the plane of the floorboards and away from the vertical joint

plane, (F) having a greater width than said locking element (8),

characterised by the combination

that said at least one operative locking surface (10)

5 of the locking element (8) is essentially plane and located at the upper part of the locking element at a distance from the upper side of the projecting strip (6) and faces the joint plane (F),

that the locking groove (14) has at least one essentially  
10 plane operative locking surface (11) which is located in the locking groove at a distance from the opening of the locking groove and which is designed to cooperate with said locking surface (10) of the locking element (8) in the joined position,

15 that the locking groove (14) at the lower edge closest to the joint plane (F) has an inclined or rounded guiding part (12) which extends from the locking surface (11) of the locking groove and to the opening of the locking groove and which is intended to  
20 guide the locking element (8) into the locking groove (14) by engaging a portion of the locking element (8) which is positioned above the locking surface (10) of the locking element or adjacent to its upper edge,

25 that said operative locking surfaces (10 and 11, respectively) of the locking element (8) and the locking groove (14) make a locking angle (A) of at least 50° to the upper side of the boards.

2. A locking system as claimed in claim 1,

30 characterised in that the floorboards (1, 1') have a core (30), a surface layer (32) on the upper side of the core and a balancing layer (34) on the rear side of the core (30).

3. A locking system as claimed in claim 1 or 2,

35 characterised in that the operative locking surfaces (10 and 11, respectively) of the locking element

(8) and the locking groove make an angle (A) of at least 60° to the upper side of the boards (1, 1').

4. A locking system as claimed in claim 3, characterised in that the operative locking surfaces (10 and 11, respectively) of the locking element (8) and the locking groove make an angle (A) of at least 80° to the upper side of the boards (1, 1').

5. A locking system as claimed in claim 4, characterised in that the operative locking surfaces (10 and 11, respectively) of the locking element (8) and the locking groove make an angle (A) of essentially 90° to the upper side of the boards (1, 1').

6. A locking system as claimed in any one of the preceding claims, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows insertion of the locking element (8) into the locking groove (14) by inward angling of one floorboard (1) towards the other floorboard (1') while maintaining contact between the joint edge surface portions (41, 42) of the two floorboards close to the border between the joint plane (F) and the upper side of the floorboards.

7. A locking system as claimed in any one of the preceding claims, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration which allows insertion of the locking element (8) into the locking groove (14) by a substantially horizontal motion of one floorboard (1) towards the other floorboard (1') during bending of the integrated strip (6) for snapping in the locking element (8) into the locking groove (14).

8. A locking system as claimed in any one of claims 1-6, characterised in that the mechanical

means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration which allows insertion of the locking element (8) into the locking groove (14) by a substantially vertical motion of one floorboard (1) towards the other floorboard (1') during bending of the integrated strip (6, 8) for snapping in the locking element (8) into the locking groove (14).

9. A locking system as claimed in any one of the preceding claims, characterised in that the relationship  $W > 0.5 H$ , where

$W$  = thickness of the locking element (8) parallel with the upper side of the floorboards on a level with the operative locking surface (19) of the locking element,

$H$  = height of the locking element (8) seen from the upper side of the strip (6).

10. A locking system as claimed in any one of claims 1-8, characterised in that the relationship  $W < 5 * H$ , where

$W$  = thickness of the locking element (8) parallel with the upper side of the floorboards on a level with the operative locking surface (19) of the locking element

$H$  = height of the locking element (8) seen from the upper side of the strip (6).

11. A locking system as claimed in any one of the preceding claims, characterised in that the locking element (8) has a thickness parallel with the upper side of the floorboards which is greater at the lower part of the locking element than at its upper part.

12. A locking system as claimed in any one of the preceding claims, characterised in that the lower guiding part (12) of the locking groove (14) and the corresponding lower part of the locking element (8)



are designed so as not to contact each other in the locked position.

13. A locking system as claimed in any one of the preceding claims, characterised in that the  
5 guiding part (12) of the locking groove (14) has a portion which is located inside a circular arc (C1), which has its centre (C3) where the joint plane (F) intersects the upper side of the floorboards (1, 1') and which is tangent to the upper part of the locking element (8).

10 14. A locking system as claimed in any one of the preceding claims, characterised in that the locking element (8) has an upper inclined or rounded guiding part (9) which is positioned above the operative locking surface (10) of the locking element (8) and  
15 outside a circular arc (C1), which has its centre (C3) where the joint plane (F) intersects the upper side of the floorboards (1, 1') and which is tangent to the upper part of the locking element (8).

15 15. A locking system as claimed in claim 13 or 14, characterised in that the sum of on the one  
20 hand the horizontal distance (E1) between a lower edge of the guiding part (12) of the locking groove (14) and said circular arc (C1) and, on the other hand, the horizontal distance (E2) between an upper edge of the guiding part  
25 (9) of the locking element (8) and said circular arc (C1) always exceeds zero, said horizontal distance (E1) for the lower edge of the locking groove being considered negative if this lower edge is located outside said circular arc (C1).

30 16. A locking system as claimed in claim 13, 14 or 15, characterised in that the guiding part (9) of the locking element (8) and the locking groove (14) are designed so as not to contact each other in the locked position.

35 17. A locking system as claimed in any one of the preceding claims, characterised in that the height of the locking element (8) and the depth of the

locking groove (14) are such that the upper part of the locking element in the locked position does not engage the locking groove.

18. A locking system as claimed in any one of the preceding claims, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows the locking element (8) to leave the locking groove (14) in upward angling of the floorboard (1') having the locking groove, while maintaining contact between the joint edge surface portions (41, 42) of the two floorboards close to the border between the joint plane (F) and the upper side of the floorboards.

19. A locking system as claimed in any one of the preceding claims, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows the floorboards (1, 1') to be displaceable parallel with the joint plane (F) in the locked position.

20. A locking system as claimed in any one of the preceding claims, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed in the joint edge portions (4a, 4b) of the floorboards.

21. A locking system as claimed in claim 18, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed as a tongue-and-groove joint.

22. A locking system as claimed in any one of the preceding claims, characterised in that the strip (6) is made of a material other than that of the core (30) of the floorboard and is integrally connected with the core.

23. A locking system as claimed in any one of claims 1-19, characterised in that the strip is made in one piece with the core (30) of the floorboard and integrally connected with the core.

- 5        24. A floorboard having a core (30) and opposing first and second joint edge portions (4a, 5a and 4b, 5b, respectively), which are designed for joining with adjoining identical floorboards by mechanical connection of the first joint edge portion (4a, 5b) of a first  
10 floorboard (1) with the second joint edge portion (4b, 5b) of an adjoining second floorboard (1') to a mechanically joined position at a vertical joint plane (F), the floorboard having a locking system which comprises
- a) for vertical joining of the first joint edge portion  
15 (4a, 5a) of a first floorboard (1) and the second joint edge portion (4a, 5a and 4b, 5b, respectively) of an adjoining second floorboard (1'), mechanical cooperating means (36, 38), and
- b) for horizontal joining of the first and second joint  
20 edge portions (4a, 5a and 4b, 5b, respectively), mechanical cooperating means (6, 8; 14) which comprise
- a locking groove (14) formed in the underside (3) of  
25 said second floorboard (1') and extending parallel with and at a distance from the vertical joint plane (F) at said second joint edge portion (4b, 5b) and having a downward directed opening, and
- a strip (6) integrally formed with the core of said  
30 first floorboard (1), which strip at said first joint edge portion (4a) projects from said vertical joint plane (F) and at a distance from the joint plane (F) has a locking element (8) which projects towards a plane containing the upper side of said first floorboard (1) and which has at  
35 least one operative locking surface (10) for coaction with said locking groove (14),

the locking groove (14), seen in the plane of the floorboards and away from the vertical joint plane (F) having a greater width than said locking element (8),

5 characterised by the combination  
that said at least one operative locking surface (10)  
of the locking element (8) is essentially plane and  
located at the upper part of the locking element at  
a distance from the upper side of the projecting  
10 strip (6) and faces the joint plane (F),  
that the locking groove (14) has at least one essentially  
plane operative locking surface (11) which is located  
in the locking groove at a distance from the  
opening of the locking groove and which is designed  
15 to cooperate with said locking surface (10) of the  
locking element (8) in the joined position,  
that the locking groove (14) at its lower edge closest  
to the joint plane (F) has an inclined or rounded  
guiding part (12) which extends from the locking  
20 surface (11) of the locking groove and to the opening  
of the locking groove and which is intended to  
guide the locking element (8) into the locking  
groove (14) by engaging a portion of the locking  
element (8) which is positioned above the locking  
25 surface (10) of the locking element or adjacent to  
its upper edge,  
that said operative locking surfaces (10 and 11, respectively)  
of the locking element (8) and the locking  
groove (14) make a locking angle (A) of at least 50°  
30 to the upper side of the boards.

25. A floorboard as claimed in claim 24, characterised in that the floorboards have a core  
(30), a surface layer (32) on the upper side of the core  
and a balancing layer (34) on the rear side of the core  
35 (30).

26. A floorboard as claimed in claim 24 or 25,  
characterised in that the operative locking

surfaces (10 and 11, respectively) of the locking element (8) and the locking groove make an angle (A) of at least  $60^\circ$  to the upper side of the boards (1, 1').

27. A floorboard as claimed in claim 26, characterised in that the operative locking surfaces (10 and 11, respectively) of the locking element (8) and the locking groove make an angle (A) of at least  $80^\circ$  to the upper side of the boards (1, 1').

28. A floorboard as claimed in claim 27, characterised in that the operative locking surfaces (10 and 11, respectively) of the locking element (8) and the locking groove make an angle (A) of essentially  $90^\circ$  to the upper side of the boards (1, 1').

29. A floorboard as claimed in any one of claims 24-28, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows insertion of the locking element (8) into the locking groove (14) by inward angling of one floorboard (1) towards the other floorboard (1') while maintaining contact between the joint edge surface portions (41, 42) of the two floorboards close to the border between the joint plane (F) and the upper side of the floorboards.

30. A floorboard as claimed in any one of claims 24-29, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows insertion of the locking element (8) into the locking groove (14) by a substantially horizontal motion of one floorboard (1) towards the other floorboard (1') during bending of the integrated strip (6) for snapping in the locking element (8) into the locking groove (14).

31. A floorboard as claimed in any one of claims 24-29, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows insertion of the locking element (8) into the locking groove (14) by a substantially vertical motion of one floorboard (1) towards the other floorboard (1') during bending of the integrated strip (6, 8) for snapping in the locking element (8) into the locking groove (14).

32. A floorboard as claimed in any one of claims 24-31, characterised in that the relationship  $W > 0.5 H$ , where

W = thickness of the locking element (8) parallel with the upper side of the floorboards on a level with the operative locking surface (19) of the locking element,

H = height of the locking element (8) seen from the upper side of the strip (6).

33. A floorboard as claimed in any one of claims 24-31, characterised in that the relationship  $W < 5 * H$ , where

W = thickness of the locking element (8) parallel with the upper side of the floorboards on a level with the operative locking surface (19) of the locking element

H = height of the locking element (8) seen from the upper side of the strip (6).

34. A floorboard as claimed in any one claims 24-33, characterised in that the locking element (8) has a thickness parallel with the upper side of the floorboards which is greater at the lower part of the locking element than at its upper part.

35. A floorboard as claimed in any one of claims 24-34, characterised in that the lower guiding part (12) of the locking groove (14) and the cor-

responding lower part of the locking element (8) are designed so as not to contact each other in the locked position.

36. A floorboard as claimed in any one of claims 5 24-35, characterised in that the guiding part (12) of the locking groove (14) has a portion which is located inside a circular arc (C1), which has its centre (C3) where the joint plane (F) intersects the upper side of the floorboards (1, 1') and which is tangent to the 10 upper part of the locking element (8).

37. A floorboard as claimed in any one of claims 24-36, characterised in that the locking element (8) has an upper inclined or rounded guiding part (9) which is positioned above the operative locking surface (10) of the locking element (8) and outside a circular arc (C1), which has its centre (C3) where the joint plane (F) intersects the upper side of the floorboards (1, 1') and which is tangent to the upper part of the 15 locking element (8).

20 38. A floorboard as claimed in claim 36 or 37, characterised in that the sum of on the one hand the horizontal distance (E1) between a lower edge of the guiding part (12) of the locking groove (14) and said circular arc (C1) and, on the other hand, the horizontal 25 distance (E2) between an upper edge of the guiding part (9) of the locking element (8) and said circular arc (C1) always exceeds zero, said horizontal distance (E1) for the lower edge of the locking groove being considered negative if this lower edge is located outside said circular arc (C1). 30

39. A floorboard as claimed in claim 36 or 37, characterised in that the guiding part (9) of the locking element (8) and the locking groove (14) are designed so as not to contact each other in the locked 35 position.

40. A floorboard as claimed in any one of claims 24-39, characterised in that the height of

the locking element (8) and the depth of the locking groove (14) are such that the upper part of the locking element in the locked position does not engage the locking groove.

5           41. A floorboard as claimed in any one of claims 24-40, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have  
10 a configuration that allows the locking element (8) to leave the locking groove (14) in upward angling of the floorboard (1') having the locking groove, while maintaining contact between the joint edge surface portions (41, 42) of the two floorboards close to the border  
15 between the joint plane and the upper side of the floorboards.

          42. A floorboard as claimed in any one of claims 24-41, characterised in that the mechanical means (36, 38) of the locking system which cooperate for  
20 vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows the floorboards (1, 1') to be displaceable parallel with the joint plane (F) in the locked position.

25           43. A floorboard as claimed in any one of claims 24-42, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed in the joint edge portions (4a, 4b) of the floorboards.

30           44. A floorboard as claimed in claim 43, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed as a tongue-and-groove joint.

          45. A floorboard as claimed in any one of claims  
35 24-44, characterised in that the strip (6) is made of a material other than that of the core (30) of the floorboard and is integrally connected with the core.



46. A floorboard as claimed in any one of claims 24-44, characterised in that the strip is made in one piece with the core (30) of the floorboard and integrally connected with the core.

- 5        47. A locking system for mechanical joining of floorboards (1, 1') having a core (30) and opposite first and second joint edge portions (5a and 5b, respectively), adjoining floorboards (1, 1') in the mechanically joined position having their first and second joint
- 10 edge portion (5a and 5b, respectively) joined at a vertical joint plane (F), said joint system comprising
- a) for vertical joining of the first joint edge portion (5a) of a first floorboard (1) and the second joint edge portion (5a and 5b, respectively) of an adjoining
- 15 second floorboard (1'), mechanical cooperating means (36, 38), and
- b) for horizontal joining of the first and second joint edge portions (5a and 5b, respectively), mechanical cooperating means (6, 8; 14) which comprise
- 20 a locking groove (14) formed in the underside (3) of said second floorboard (1') and extending parallel with and at a distance from the vertical joint plane (F) at said second joint edge portion (5b) and having a downward directed opening, and
- 25 a strip (6) integrally formed with the core of said first floorboard (1), which strip at said first joint edge portion (5a) projects from said vertical joint plane (F) and at a distance from the joint plane (F) has a locking element (8) which
- 30 projects towards a plane containing the upper side of said first floorboard (1) and which has at least one operative locking surface (10) for coaction with said locking groove (14),
- the locking groove (14), seen in the plane of the
- 35 floorboards and away from the vertical joint plane (F), having a greater width than said locking element (8),

characterised by the combination

that said at least one operative locking surface (10)  
of the locking element (8) is essentially plane and  
located at the upper part of the locking element at  
a distance from the upper side of the projecting  
strip (6) and faces the joint plane (F),

that the locking groove (14) has at least one essentially  
plane operative locking surface (11) which is located  
in the locking groove at a distance from the  
opening of the locking groove and which is designed  
to cooperate with said locking surface (10) of the  
locking element (8) in the joined position,

that the operative locking surfaces (10 and 11, respectively)  
of the locking element (8) and the locking  
groove (14) have a locking angle (A) which is essentially  
perpendicular to the upper side of the floor-boards,

that the operative locking surfaces (10 and 11, respectively)  
of the locking element (8) and the locking  
groove (14) have a height (LS) parallel with the  
joint plane (F) which is less than 0.5 times the  
height (H) of the locking element (8),

that the locking groove (14) at its lower edge closest to  
the joint plane (F) has an inclined or rounded guiding  
part (13) which extends from the locking surface  
(11) of the locking groove and to the opening of the  
locking groove, and

that the locking element (8) at its upper end has an  
inclined or rounded guiding part (9) extending from  
the operative locking surface (10) of the locking  
element and adapted to engage with the guiding part  
(12) of the locking groove during guiding of the  
locking element (8) into the locking groove (14).

48. A locking system as claimed in claim 47,

characterised in that the sum of on the one  
hand the horizontal distance (E1) between a lower edge  
of the guiding part (12) of the locking groove (14) and a

circular arc (C1), which has its centre (C3) where the joint plane (F) intersects the upper side of the floorboards (1, 1') and which is tangent to the upper part of the locking element (8) and, on the other hand, the horizontal distance (E2) between an upper edge of the guiding part (9) of the locking element (8) and said circular arc (C1) always exceeds zero, said horizontal distance (E1) for the lower edge of the locking groove being considered negative if this lower edge is located outside said circular arc (C1).

49. A locking system as claimed in claim 47 or 48, characterised in that the floorboards (1, 1') have a core (30), a surface layer (32) on the upper side of the core and a balancing layer (24) on the rear side of the core (30).

50. A locking system as claimed in claim 47, 48 or 49, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows insertion of the locking element (8) into the locking groove (14) by a substantially horizontal motion of one floorboard (1) towards the other floorboard (1') during bending of the integrated strip (6) for snapping in the locking element (8) into the locking groove (14).

51. A locking system as claimed in any one of claims 47-50, characterised in that the lower guiding part (12) of the locking groove (14) and the corresponding lower part of the locking element (8) are designed so as not to contact each other in the locked position.

52. A locking system as claimed in any one of claims 47-51, characterised in that the locking element (8) has an upper guiding part (9) which is positioned above the operative locking surface (10) of the locking element (8) and further away from said centre (C3)

than the circular arc (C1) which is tangent to the upper end of the locking element (8).

53. A locking system as claimed in claim 52, characterised in that the guiding part (9) of the locking element (8) and the locking groove (14) are designed so as not to contact each other in the locked position.

54. A locking system as claimed in any one of claims 47-53, characterised in that the height of the locking element (8) and the depth of the locking groove (14) are such that the upper part of the locking element in the locked position does not engage with the locking groove.

55. A locking system as claimed in any one of claims 47-54, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical joining and the means (6, 8; 14) of the locking system which cooperate for horizontal joining have a configuration that allows the floorboards (1, 1') to be displaceable parallel with the joint plane (F) in the locked position.

56. A locking system as claimed in any one of claims 47-55, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed in the joint edge portions (5a, 5b) of the floorboards.

57. A locking system as claimed in claim 56, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed as a tongue-and-groove joint.

58. A locking system as claimed in any one of claims 43-52, characterised in that the strip is made of a material other than that of the core (30) of the floorboard and is integrally connected with the core.

59. A locking system as claimed in any one of claims 47-58, characterised in that the strip is

made in one piece with the core (30) of the floorboard and integrally connected with the core.

60. A floorboard comprising a core (30) and opposite first and second joint edge portions (5a and 5b, respectively) which are designed for joining with adjoining floorboards by mechanical connection of the first joint edge portion (5a) of a first floorboard (1) with the second joint edge portion (5b) of an adjoining second floorboard (1') to a mechanically joined position at a vertical joint plane, the floorboard having a locking system which comprises

- a) for vertical joining of the first joint edge portion (5a) of a first floorboard (1) and the second joint edge portion (5a and 5b, respectively) of an adjoining second floorboard (1'), mechanical cooperating means (36, 38), and
  - b) for horizontal joining of the first and second joint edge portions (5a and 5b, respectively), mechanical cooperating means (6, 8; 14) which comprise
    - a locking groove (14) formed in the underside (3) of said second floorboard (1') and extending parallel with and at a distance from the vertical joint plane (F) at said second joint edge portion (5b) and having a downward directed opening, and
    - a strip (6) integrally formed with the core of said first floorboard (1), which strip at said first joint edge portion (5a) projects from said vertical joint plane (F) and at a distance from the joint plane (F) has a locking element (8) which projects towards a plane containing the upper side of said first floorboard (1) and which has at least one operative locking surface (10) for coaction with said locking groove (14),
- the locking groove (14), seen in the plane of the floorboards and away from the vertical joint plane, (F) having a greater width than said locking element (8),

characterised by the combination  
that said at least one operative locking surface (10)  
of the locking element (8) is essentially plane and  
located at the upper part of the locking element at  
5 a distance from the upper side of the projecting  
strip (6) and faces the joint plane (F),  
that the locking groove (14) has at least one essentially  
plane operative locking surface (11) which is located  
in the locking groove at a distance from the  
10 opening of the locking groove and which is designed  
to cooperate with said operative surface (10) of the  
locking element (8) in the joined position,  
that the operative locking surfaces (10 and 11, respectively)  
of the locking element (8) and the locking  
15 groove (14) have a locking angle (A) which is essentially  
perpendicular to the upper side of the floorboards,  
that the operative locking surfaces (10 and 11, respectively)  
of the locking element (8) and the locking  
20 groove (14) have a height (LS) parallel with the  
joint plane (F) which is less than 0.5 times the  
height (H) of the locking element (8),  
that the locking groove (14) at its lower edge closest to  
the joint plane (F) has an inclined or rounded guiding  
25 part (12) which extends from the locking surface  
(11) of the locking groove and to the opening of the  
locking groove, and  
that the locking element (8) at its upper end has an  
inclined or rounded guiding part (9) extending from  
30 the operative locking surface (10) of the locking  
element and adapted to engage with the guiding part  
(12) of the locking groove during guiding of the  
locking element (8) into the locking groove (14).  
61. A floorboard as claimed in claim 60, characterised  
35 in that the sum of on the one hand the  
horizontal distance (E1) between a lower edge of the  
guiding part (12) of the locking groove (14) and a circu-

lar arc (C1), which has its centre (C3) where the joint plane (F) intersects the upper side of the floorboards (1, 1') and which is tangent to the upper part of the locking element (8) and, on the other hand, the horizontal distance (E2) between an upper edge of the guiding part (9) of the locking element (8) and said circular arc (C1) always exceeds zero, said horizontal distance (E1) for the lower edge of the locking groove being considered negative if this lower edge is located outside said circular arc (C1).

62. A floorboard as claimed in claim 60 or 61, characterised in that the floorboards (1, 1') have a core (30), a surface layer (32) on the upper side of the core and a balancing layer (24) on the rear side of the core (30).

63. A floorboard as claimed in claim 60, 61 or 62, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical locking and the means (6, 8; 14) of the locking system which cooperate for horizontal locking have a configuration that allows insertion of the locking element (8) into the locking groove (14) by a substantially horizontal motion of one floorboard (1) towards the other floorboard (1') during bending of the integrated strip (6) for snapping in the locking element (8) into the locking groove (14).

64. A floorboard as claimed in any one of claims 60-63, characterised in that the lower guiding part (12) of the locking groove (14) and the corresponding lower part of the locking element (8) are designed so as not to contact each other in the locked position.

65. A floorboard as claimed in any one of claims 60-64, characterised in that the height of the locking element (8) and the depth of the locking groove (14) are such that the upper part of the locking

element in the locked position does not engage with the locking groove.

5 66. A floorboard as claimed in any one of claims 60-65, characterised in that the mechanical means (36, 38) of the locking system which cooperate for vertical joining and the means (6, 8; 14) of the locking system which cooperate for horizontal joining have a configuration that allows the floorboards (1, 1') to be displaceable parallel with the joint plane (F) in the  
10 locked position.

67. A floorboard as claimed in any one of claims 60-66, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed in the joint edge portions (5a, 5b) of the  
15 floorboards.




68. A floorboard as claimed in claim 67, characterised in that the mechanical means (36, 38) for vertical joining of the floorboards are formed as a tongue-and-groove joint.

20 69. A floorboard as claimed in any one of claims 60-68, characterised in that the strip (6) is made of a material other than that of the core (30) of the floorboard and integrally connected with the core.




70. A floorboard as claimed in any one of claims  
25 60-68, characterised in that the strip is made in one piece with the core (30) of the floorboard and integrally connected with the board.

71. A flooring formed by joining floorboards according to any one of claims 24-46 and 60-70.





PRIOR ART



PRIOR ART

Fig. 3a





Fig. 3b



PRIOR ART

Fig. 4a




Fig. 4b




Fig. 4c




Fig. 4d






Fig. 4e




PRIOR ART

*Fig. 5*



PRIOR ART

*Fig. 6*



PRIOR ART





Fig. 11





Fig. 12



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 01/00779

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: E04F 15/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: E04F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9426999 A1 (VÄLINGE ALUMINIUM AB), 24 November 1994 (24.11.94), abstract, details 10, 34 --	1-71
A	WO 9747834 A1 (UNILIN BEHEER B.V.), 18 December 1997 (18.12.97), abstract, details 31, 49 --	1-71
A	GB 2256023 A (MAGNET HOLDINGS LIMITED), 25 November 1992 (25.11.92), abstract --	1-71
A	WO 9824994 A1 (VÄLINGE ALUMINIUM AB), 11 June 1998 (11.06.98), abstract --	1-71

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier application or patent but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

15 June 2001

Date of mailing of the international search report

20 -06- 2001

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Örjan Nylund / MRo

Telephone No. +46 8 782 25 00



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 01/00779

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 9824995 A1 (VÄLINGE ALUMINIUM AB), 11 June 1998 (11.06.98), abstract  --	1-71
A	US 4426820 A (TERBRACK ET AL), 24 January 1984 (24.01.84)  -- -----	1-71

INTERNATIONAL SEARCH REPORT  
Information on patent family members

28/05/01

International application No.

PCT/SE 01/00779

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9426999 A1	24/11/94	AT 171238 T	15/10/98
		AT 187222 T	15/12/99
		AT 189287 T	15/02/00
		AU 671919 B	12/09/96
		AU 6763094 A	12/12/94
		BG 61457 B	29/08/97
		BG 100126 A	28/06/96
		BR 9406718 A	06/02/96
		CA 2150384 A	24/11/94
		CN 1122623 A	15/05/96
		CN 1285447 A	28/02/01
		CN 1285448 A	28/02/01
		CZ 9502852 A	15/05/96
		DE 69413391 D,T	04/02/99
		DE 69421945 D,T	27/04/00
		DE 69422838 D,T	15/06/00
		DK 698162 T	28/12/98
		EP 0698162 A,B	28/02/96
		SE 0698162 T3	
		EP 0855482 A,B	29/07/98
		SE 0855482 T3	
		EP 0877130 A,B	11/11/98
		SE 0877130 T3	
		EP 0969163 A	05/01/00
		EP 0969164 A	05/01/00
		EP 1061201 A	20/12/00
		ES 2122280 T	16/12/98
		ES 2140983 T	01/03/00
		ES 2141630 T	16/03/00
		FI 951211 A	15/03/95
		FI 20001601 A	04/07/00
		FI 20001602 A	04/07/00
		GR 3032335 T	27/04/00
		GR 3032392 T	31/05/00
		HU 75843 A	28/05/97
		HU 214470 B	30/03/98
		HU 9503216 D	00/00/00
		JP 8510022 T	22/10/96
		JP 2001032382 A	06/02/01
		JP 2001032383 A	06/02/01
		JP 2001040860 A	13/02/01
		JP 2001049844 A	20/02/01
		LV 11491 A,B	20/08/96
		NO 305614 B	28/06/99
		NO 950790 A	22/05/95
		NO 986137 A	22/05/95
		NO 993136 A	24/06/99
		NZ 266232 A	26/11/96
		PL 311568 A	19/02/96
		PT 877130 T	28/04/00
		RO 115185 A,B	30/11/99
		RU 2123094 C	10/12/98
		SE 501014 C	17/10/94
		SE 9301595 A	17/10/94
		SG 47518 A	17/04/98

INTERNATIONAL SEARCH REPORT  
Information on patent family members

28/05/01

International application No.  
PCT/SE 01/00779

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
WO	9426999	A1	24/11/94	SK	141195 A	06/11/96
				US	5706621 A	13/01/98
				US	5860267 A	19/01/99
				US	6023907 A	15/02/00
				US	6182410 B	06/02/01
WO	9747834	A1	18/12/97	AT	196790 T	15/10/00
				AU	713628 B	09/12/99
				AU	3256997 A	07/01/98
				BE	1010339 A	02/06/98
				BE	1010487 A	06/10/98
				BG	62216 B	31/05/99
				BG	102230 A	30/09/98
				BR	9702325 A	09/03/99
				CA	2226286 A	18/12/97
				CN	1195386 A	07/10/98
				CZ	9800391 A	12/08/98
				DE	29710175 U	14/08/97
				DE	29724428 U	05/04/01
				DE	69703230 D,T	01/03/01
				DK	843763 T	29/01/01
				EP	0843763 A,B	27/05/98
				SE	0843763 T3	
				EP	1024234 A	02/08/00
				EP	1026341 A	09/08/00
				ES	2152679 T	01/02/01
				ES	2153799 T	16/03/01
				ES	2153800 T	16/03/01
				HU	9901996 A	28/10/99
				JP	11510869 T	21/09/99
				NO	980569 A	10/02/98
				PL	324923 A	22/06/98
				PT	843763 T	30/03/01
				SI	9720009 A	31/08/98
				SK	16398 A	09/09/98
				TR	9800209 T	00/00/00
				US	6006486 A	28/12/99
GB	2256023	A	25/11/92	GB	9110787 D	00/00/00
WO	9824994	A1	11/06/98	AU	5422398 A	29/06/98
				EP	0958441 A	24/11/99
				NO	992653 A	09/07/99
				SE	509060 C	30/11/98
				SE	9604484 A	06/06/98
				US	6205639 B	27/03/01
WO	9824995	A1	11/06/98	AU	5422498 A	29/06/98
				EP	0958442 A	24/11/99
				SE	509059 C	30/11/98
				SE	9604483 A	06/06/98
				US	6094882 A	01/08/00
US	4426820	A	24/01/84	DE	7928703 U	02/07/81